

## Car Hauler Trailers



**7 X 18**    **7 X 20**  
 7000 Lbs.   7000 Lbs.  
 9990 Lbs.   9990 Lbs.

**Steel Deck**



**Optional Removable Teardrop Fenders**

**Sure-Trac Car Hauler Trailers** – The frame is structural 5" tubing with heavy duty, 16 inch on center crossmembers. We offer MaxiStrength™ stitch welded diamond plate steel decking. The air-dam bulkhead and D-Ring tie downs provide a smooth and secure ride. The engineered tailboard has sealed recessed lights. This trailer incorporates the best available construction, material and overall fit and finish.



**Sealed Lights** – DOT approved lights and reflective tape.



**Optional 7000 Lb Set-Back Tongue Jack** – Provides clearance for Tailgate and SUV Rear Doors.



**Slide In Ramps** – Heavy-duty, 5 ft. ramps and beavertail for low clearance vehicles.



**Ramp Compartments** – Ramps fit neatly under deck for fast loading and unloading.

**Check out these other great features:**

- EZ-Lube Hubs
- MaxiStrength™ Welds
- True-Trac Alignment
- Conduit Protected Wiring
- Gel-Filled Connectors
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts



**Stake Pockets & Rub Rail** – Full length on both sides.



**Teardrop Fenders** – With backers allow for a clean ride and smooth good looks.



**5K Lbs. D-Ring tie Downs** – At each corner provide easy load securement.



**New Tires Wheels and Axles** – Sure-Trac trailers have all new tires, wheels, and axles. In many states it is illegal to sell new trailers with used running gear.

**Powder Coated Finish** – All Sure-Trac trailers are powder coated for a durable high-gloss finish that will last for years.



CAR HAULER TRAILERS SPECIFICATIONS				
	7000 Lb 7 X 18 Steel	9990 Lb 7 X 18 Steel	7000 Lb 7 X 20 Steel	9990 Lb 7 X 20 Steel
<b>GVWR (Lbs)</b>	7000	9990	7000	9990
<b>GAWR (Lbs/Axle)</b>	3500	5000	3500	5000
<b>Curb Weight</b>	1920	2140	2070	2400
<b>Payload</b>	5080	7850	4930	7590
<b>Max Hitch Weight</b>	700	1000	700	1000
<b>Frame</b>	5 Inch Tubing			
<b>Cross Members</b>	2 x 2 Tubing	3 Inch C-Channel	2 x 2 Tubing	3 Inch C-Channel
<b>Tongue</b>	2 x 5 Full wrap Tubing			
<b>Coupler</b>	2" Ball	2-5/16" Ball	2" Ball	2-5/16" Ball
<b>Jack</b>	2000 Lb Top Wind	5000 Lb Top Wind	2000 Lb Top Wind	5000 Lb Top Wind
<b>Fenders</b>	Teardrop			
<b>Axles</b>	Cambered Brake and Idler	Cambered Brake Both Axles	Cambered Brake and Idler	Cambered Brake Both Axles
<b>Easy Lube Axle</b>	Greaseable hubs on both axles			
<b>Suspension</b>	Double Eye Leaf Spring			
<b>Tires</b>	205/75D15 LRC	225/75D15 LRD	205/75D15 LRC	225/75D15 LRD
<b>Wheels</b>	15 In, 5 on 4.5	15 In, 6 on 5.5	15 In, 5 on 4.5	15 In, 6 on 5.5
<b>Floor</b>	1/8 Tread Plate			
<b>Lights</b>	Sealed DOT Stop, Tail and Turn, Clearance and Reflective Marking			
<b>Electric Plug</b>	7 Way Round			
<b>Finish</b>	Powder Coated High Gloss Black			
<b>Overall Length</b>	22'		24'	
<b>Bed Length Flat</b>	14'		16'	
<b>Drop Length</b>	4'			
<b>Bed Width</b>	82"			
<b>Floor Height</b>	21-1/2"	23"	21-1/2"	23"
<b>Coupler Height</b>	17"	18"	17"	18"
<b>Ramps</b>	5' Fabricated 10 Ga	5' Reinforced 10 Ga	5' Fabricated 10 Ga	5' Reinforced 10 Ga

OPTIONS	
<b>Spare Tire</b>	Matching Tire and Rim Also Available U-Bolt Carrier
<b>Brake Axle</b>	Second Brake Axle      N/A
<b>Jack</b>	Heavy Duty, 7000 Lb Frame Welded Drop-leg Jack with Foot Plate

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.