SURE-TRAC™ The Professional Advantage™

DECKOVER EQUIPMENT TRAILER SPECIFICATIONS				
	12K	**14K**	**20K**	**24K**
	8.5 X 17 + 3	**8.5 X 20 + 5**		
Type	**Pintle**			
GVWR (Lbs.)	12000	14000	20000	24000
GAWR (Lbs./Axle)	6000	7000	10000	12000
Curb Weight	3720	4640	5720	5840
Payload	8280	9360	14280	18120
Max Hitch Weight	1200	1400	2000	2400
Main Frame	W6 x 9#/ft, I-Beam	W10 x 12#/ft,I-Beam	W10 x 19#/ft,I-Beam	W10 x 19#/ft,I-Beam
Cross Members	3" C-Channel			
Tongue	Cold Formed Main Beam			
Side Rails	5" C-Channel		6" C-Channel	
Beaver Tail	Self-Cleaning Cleats			
Coupler	5 Position Adjustable		3 Position Adjustable	
Jack	Center Mounted 12K Binkley Drop Leg			
Axles	E-Z Lube Electric Brake		Oil Bath Bearing	
Suspension	Eye to Eye	Slipper Leaf Spring		
Tires	7.5/16LT LRF Bias	235/80R16 LRE		
Wheels	16			
	White, Modular or Spoke		Grey	
Decking	2" Pressure Treated Pine			
Lights	Sealed Recessed DOT Lighting, Side Markers, Stop, Tail, Turn, Marking, Clearance and Conspicuity Treatment			
Electric Plug	7 Way Round			
Finish	5-Step Process, High Gloss Industrial Paint and Primer Finish			
Overall Length	26.5	30.5	31.5	31.5
Deck Height	36			
Coupler Height	Adjustable 19"-27"	Adjustable 21"-29"		
Ramps	3" C-Channel with Spring Assist	HD Fabricated Fold Flat with Double Hinged spring assist		

OPTIONS

	12K	**14K**	**20K**	**24K**
Wheel Upgrades	235/80R16 LRE	LT235/85R16 LRG		
Spare Tire Option	Matching Tire and Rim			
Suspension	Slipper Spring	Torsion Axle	N/A	
Decking	2" Oak Decking W/Bolt Down Center Board Retainer			
Frame Add Ons	Mesh Tool Basket Built Into Tongue/Mesh Tool Basket Between Gooseneck Uprights			
	Under Bed Toolbox/Gooseneck Toolbox			
	Gooseneck			
Coupler	2-5/16 Ball Coupler			
Body Options	Mud Flaps			
	LED Lighting			