

Heavy Duty Deckover Trailers

Sizes
Up To 48 ft. Length
(8 X 20+5 Shown)

GVWRs
Up To 26,000 Lbs.
(14K GVWR Shown)



**Optional Gooseneck
Toolbox**

Trailer Pictured With Additional
Optional Features.

**Bumper Pull and
Gooseneck Option
Available**

DeckStender[™] Ramps – Provide
An Additional 5 ft. of Deck.



Sure-Trac HD Deckover Trailers – Our trailers are built with incredible attention to detail and craftsmanship, and designed for a lifetime of hard work. Our innovative Cross Trac[™] support design helps to stabilize the trailer, transferring extreme loads evenly to the frame.

Check out these other great features:

- Spare Tire Carrier and Side Steps Standard
- Pressure Treated Decking
- DOT Approved SEALED Lights and Conspicuity Tape
- True-Trac[™] Alignment
- New Tires, Wheels & Axles
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping



Ramp Spring Assist – User friendly and standard on all beaver tail models.



Heavy Duty Ramps – Rugged fabricated construction with support foot.



5K Lbs. D-Ring Tie Downs – Comes standard with Four Heavy Duty D-rings.



Stake Pockets & Rub Rail – Heavy duty design provides expandability and protection on side loading jobs.



Pintle Eye Coupler – 3 or 5 positions for maximum flexibility.



Heavy Duty C-channel Deck Frame – With massive I-beam frame members, withstands the heaviest of loads.



Mesh Open Tool Storage – Optional on all sizes.



HD Frame-Mounted Jack – 4-3/8" Binkley Jack standard.


Novae[®]
NovaeCorp.com

800-372-1755

HEAVY DUTY DECKOVER TRAILER SPECIFICATIONS				
	12k	14k	20k	24k
	8.5 x 17 + 3	8.5 x 20 + 5		
Type	Pintle			
GVWR (Lbs.)	12000	14000	20000	24000
GAWR (Lbs./Axle)	6000	7000	10000	12000
Curb Weight	3720	4640	5720	5840
Payload	8280	9360	14280	18120
Max Hitch Wt.	1200	1400	2000	2400
Main Frame	W6 x 9#/ft, I-Beam	W10 x 12#/ft, I-Beam	W10 x 19#/ft, I-Beam	W10 x 19#/ft, I-Beam
Crossmembers	3" C-Channel			
Tongue	Cold Formed Main Beam			
Side Rails	5" C-Channel		6" C-Channel	
Beaver Tail	Self-Cleaning Cleats			
Coupler	5 Position Adjustable		3 Position Adjustable	
Jack	Center Mounted 12k Binkley Drop Leg			
Axles	E-Z Lube Electric Brake		Oil Bath Bearing	
Suspension	Eye to Eye	Slipper Leaf Spring		
Tires	7.5/16LT LRF Bias	235/80R16 LRE		
Wheels	16			
	White, Modular or Spoke		Grey	
Decking	2" Pressure Treated Pine			
Lights	Sealed Recessed DOT Lighting, Side Markers, Stop, Tail, Turn, Marking, Clearance and Conspicuity Treatment			
Electric Plug	7 Way Round			
Finish	5-Step Process, High Gloss Industrial Paint and Primer Finish			
Overall Length	26.5	30.5	31.5	31.5
Deck Height	36			
Coupler Height	Adjustable 19"-27"	Adjustable 21"-29"		
Ramps	3" C-Channel with Spring Assist	HD Fabricated Fold Flat with Double hinged spring assist		
OPTIONS				
	12k	14k	20k	24k
Wheel Upgrades	235/80R16 LRE	LT235/85R16 LRG		
Spare Tire Option	Matching Tire and Rim			
Suspension	Slipper Spring	Torsion Axle	N/A	
Decking	2" Oak Decking W/ Bolt Down Center Board Retainer			
Frame Add Ons	Mesh Tool Basket Built Into Tongue/Mesh Tool Basket Between Gooseneck Uprights			
	Under Bed Toolbox/Gooseneck Toolbox			
	Gooseneck			
Coupler	2-5/16 Ball Coupler			
Body Options	Mud Flaps			
	LED Lighting			

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.

Novae® 800-372-1755
www.sure-trac.com