

HD Series Dump Trailers

Sizes
6 X 10
7,000 Lbs.

6 X 10
10,000 Lbs.

7 X 12
12,000 Lbs.

7 X 14
14,000 Lbs.

7 X 16
14,000 Lbs.



6 x 10 Deckover Dump – Perfect for the homeowner or light duty construction.



Sure-Trac HD Series Dump Trailers – Our most competitive dump trailer ever built is a smart combination of features, durability and value. These trailers have everything the hard working contractor is looking for in a package that is ready for your toughest jobs. We utilize heavy 11 gauge DuraSteel™ construction with full seam welds in the bed for ultimate strength and product flow. These Heavy-Duty Dump trailers will provide years of reliable service.



Optional Stabilift™ Heavy-Duty Hydraulic Scissor Hoist.



Multi-Function Gate – Easily convert barn doors to spreader gate with **Heavy Duty, Single Handle Spreader Gate Latch.**



HD Ladder Ramps – Easy access 5 ft. ramps allow for smooth loading/unloading of equipment (Optional on 6 x 10).



Custom Pump/Battery Box – Lockable Self-latching custom box and long-lasting marine battery. **Control Switch** operates lift up to 20 ft. away.

Check out these other great features:

- True-Trac™ Alignment
- Easy Lube Hubs (10K & up)
- Torsion Axles (Optional)
- Powder Coated Finish
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping



Full Seam Welds – On all frame joints ensure structural integrity throughout the frame.



Spare Tire Holder – Securely attach a spare tire to the front of the trailer (Optional on 6 X 10).



Slat Holder – Drop in a 2 x 12 to easily increase the side height of your trailer.

HD SERIES DUMP TRAILER SPECIFICATIONS

| | 6 x 10 Deckover | 6 x 10 Low Profile | 80" x 12 Low Profile | 80" x 14 Low Profile | 80" x 16 Low Profile |
|--------------------------------|---|--|-------------------------|-------------------------|-------------------------|
| GVWR (Lbs.) | 7000 | 9990 | 12000 | 14000 | 14000 |
| GAWR (Lbs./Axle) | 3500 | 5000 | 6000 | 7000 | 7000 |
| Curb Weight | 1820 | 3200 | 3240 | 3600 | 3960 |
| Payload | 5180 | 6790 | 8760 | 10400 | 10040 |
| Max Hitch Wt. | 700 | 1000 | 1200 | 1400 | 1400 |
| Frame | 2 x 4 Tubing | 2 x 5 Tubing | | 2 x 6 Tubing | |
| Crossmembers | 2 x 4 Tube | | | | |
| Tongue | A-Frame 2 x 4 Tube | A-Frame 2 x 5 Tube | | | |
| Sides | 11 GA. 20" | 11 GA. 24" | | | |
| Coupler | 2-5/16" A-Frame Ball Coupler | | | | |
| Jack | Coupler Mounted, 2000# Top Wind | | | | |
| Fenders | N/A | Heavy Duty Treadplate | | | |
| Axles | Cambered Brake | | | | |
| Suspension | Equalized Leaf Spring | | | | |
| Tires | 205/75D15 LRD | 225/75D15 LRD | 750-16LT LRF | 235/80R16 LRE | |
| Wheels | 5 on 4.5 | 15", 5 on 4.5 | 16", 8 on 6.5 | | |
| | White, Spoke or Modular | | | | |
| Floor | 11 GA | | | | |
| Lights | DOT Approved | Sealed Recessed DOT Lighting Side Markers Stop Turn Tail and Conspicuity Treatment | | | |
| Electric Plug | 7 Way Round | | | | |
| Finish | Powder Coated High Gloss Black | | | | |
| Overall Length (in.) | 159 | 174 | 198 | 222 | 246 |
| Bed Length Inside (in.) | 120 | 120 | 144 | 168 | 192 |
| Bed Width Inside (in.) | 71.5 | | 80 | | |
| Bed Height Inside (in.) | 16 | 24 | | | |
| Floor Height (in.) | 33 | 29 | | | |
| Coupler Height (in.) | 21 | 19 | | | |
| Gate | Fold Down | 2 Way Combination Spreader/Barn | | | |
| Hydraulic Hoist | Single Ram | Dual Ram | | | |
| Pump | 2500 PSI 12VDC With Hydraulic Reservoir | | | | |
| Battery | 24 Group Deep Cycle Battery | | | | |

OPTIONS

| | 6 x 10 | 6 x 10 | 80" x 12 | 80" x 14 | 80" x 16 |
|--------------------------|---|---------------|---------------|----------|----------|
| Wheel Upgrades | 225/75D15 LRD | 235/80R16 LRE | 235/80R16 LRE | N/A | |
| Spare Tire Option | Matching Tire and Rim | | | | |
| Suspension | Slipper Leaf Spring | | | | |
| Ramps | Heavy 3" C-Channel Ramps with Fender Storage (Standard on 80" x 12) | | | | |
| Axle Option | Torsion | | | | |
| Frame Add Ons | Mesh Tool Basket Built Into Tongue | | | | |
| | Power Up/Down Pump | | | | |
| Coupler | 2-5/16 Adjustable Ball Coupler | | | | |
| Body Options | (5) 5000lb D-Rings Welded Into Bed (Standard on 80" x 12) | | | | |
| | Spare Tire Mount (Standard on 80" x 12) | | | | |
| Hoist | Scissor Hoist | | | | |

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.