

High Side Trailers

4.5 X 8
2,000 Lbs.

5 X 8
3,000 Lbs.*

5 X 10
3,000 Lbs.*
5,000 Lbs.

7 X 12
3,000 Lbs.*
5,000 Lbs.

7 x 16
7,000 Lbs.
10,000 Lbs.*



*Actual GVWR listed on spec sheet.

Sure-Trac High Side Trailers – These trailers have solid steel sides 14 inches tall with a tube frame tie down rail and 3500 lb. EZ-Lube axles, ready for the toughest jobs in landscaping, construction, or heavy duty homeowner applications. The tongues are made with heavy structural C-channel.



Check out these other great features:

- EZ-Lube Hubs
- Pressure Treated Decking (Optional)
- DOT Approved Protected Lights and Conspicuity Tape
- True-Trac[™] Alignment
- New Tires, Wheels and Axles
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping



Wrap Around Tongue – Full 4 inch wrap on all 7 ft. wide trailers.



Fold Flat Tube Frame Ramp Gate – 20% lighter and 40% stronger!



Finished Corners – Integrated into the structural frame work. Adds strength, durability and smooth good looks.



Self-Retained Gate Pins – Fast, reliable and never lost.



Set-Back Tongue Jack – Clearance for tailgate and SUV rear doors.



Full Seam Welds – On all joints ensure structural integrity throughout the frame.



Protected Wiring – Wires in frame tubes with corrosion resistant Gel-Filled Connectors.



Powder Coated Finish – A durable high-gloss finish that will last for years.


Novae[®]
NovaeCorp.com

800-372-1755

WWW.SURE-TRAC.COM 800-372-1755

HIGH SIDE TRAILER SPECIFICATIONS					
	4.5 x 8	5 x 8	5 x 10	7 x 12	7 x 16
GVWR	2000	2990			7000
GAWR	2000	3500			
Curb Weight	780	960	1020	1480	2160
Payload	1220	2030	1970	1510	4840
Max Hitch Wt.	200	300			700
Crossmembers	3 x 2 x 3/16 Angle				
Tongue	3 X 2 tubing	A-Frame 3 Inch C-Channel		Wrap Around A-Frame 4 Inch C-Channel	
Frame/Sides	14 GA. 24" High Fabricated				
Coupler	2" Ball			2-5/16" Ball	
Jack	N/A	Top Wind 2000#			
Fenders	Square Rolled with Back			Teardrop Rolled with Back	
EZ-Lube Axles	Cambered Idler			Cambered Brake & Idler	
Suspension	Leaf Spring			Equalized Leaf Spring	
Tires	175/80D13 LRC	205/75D15LRC			
Wheels	13",5 on 4.5	15",5 on 4.5			
	White, Spoke or Modular				
Floor	2" Pressure Treated Pine				
Lights	DOT Stop, Tail, Turn and Marking			DOT Stop, Tail, Turn, Marking and Clearance	
Electric Plug	4 Way Plug			7 Way Round	
Finish	Powder Coated High Gloss Black				
Overall Length	137"		161"	185"	233"
Bed Length	96"		120"	144"	192"
Bed Width	54"	61.5"			81.5"
Floor Height	16"	18"			
Coupler Height	14"	16"			
Gate	2 x 2 Tubing, #9, 3/4" Raised Mesh Covered, Full Width Ramp Gate				
OPTIONS					
Wheel Upgrades	205/D15 LRC	225/75D15 LRD			
Spare Tire Option	Matching Tire and Rim				
Brake Upgrades	Includes Breakaway Kit, 7 Way Plug, Brake Axle			Includes second Brake Axle	
Axle Upgrades	N/A	EZ-Lube, 5000 Lbs.			EZ-Lube, 10000 Lbs.

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.