

Implement Trailers

Sizes

- 7 X 16
- 7 X 18
- 7 X 20

GVWR

- 10000 Lbs.
- 12000 Lbs.
- 14000 Lbs.

Flat Base Ramps - Asphalt friendly design features unique flat base, 3" C-channel construction and support foot.

Shown with Optional Forest Green Color.



Sure-Trac Implement Trailers - The frame is heavy duty structural C-channel with 3 inch channel cross members. The attention to detail in design and construction is unmatched with features like stake pockets & rub rail, sealed recessed lights, side steps, and a full frame wrap tongue. It all adds up to the best implement trailer value you can find.

Check out these other great features:

- True-Trac™ Alignment
- 12 GA Tread Plate Fenders
- Conduit Protected Wiring
- Gel-Filled Connectors
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping



Sealed Recessed Lights
- DOT approved lights and reflective tape.



Optional Gooseneck Available



Full Seam Welds - On all joints ensure structural integrity throughout the frame.



HD 1/4" Stake Pockets
- and full-length rub rail.



Optional 7000 lb. Drop-Leg-Jack - This rugged design doubles as a spare tire mount.



HD 5 Ton D-Rings
- Welded at each corner.



New Tires, Wheels and Axles - In many states it is illegal to sell new trailers with used running gear.



Powder Coated Finish - A durable high-gloss finish that will last for years.

Novae

1-800-372-1755

IMPLEMENT TRAILERS SPECIFICATIONS			
	10K	12K	14K
GVWR	9990	12000	14000
GAWR	5200	6000	7000
Curb Weight	16	2550	2650
	18	2750	2850
	20	2950	3050
Payload	16	7440	9350
	18	7240	9150
	20	7040	8950
Max Hitch Weight	1000	1200	1400
Frame	5" C-Ch.	6" C-Channel	
Cross Members	2 ft. On-Ctr	3" C-Ch. (16 On-Ctr)	
Tongue	5" C-Ch.	6" C-Channel	
Coupler	2 5/16 A-Frame		
Jack	Coupler Mounted Jack		
Fenders	HD Tread Plate		
Axles	Easy Lube Cambered Brake		
Suspension	Eye to Eye Spring		
Tires	225/75D15	7.5-16	235/80*16
	(D) Bias	Bias	(R) Radial
	LRD	LRF	LRE
Wheels	6 Lug on 5.5	8 Lug on 6.5	
	16 X 6K, White or Grey, Modular		
Floor	2X6 Treated Pine		
Lights	Rubber Mounted/Sealed DOT stop, Tail, Turn, Marking and Clearance.		
Electric Plug	7 Way Round		
Finish	Powder Coated High Gloss		
Length Overall/Flat	16	21' 9" / 14'	
	18	23' 9" / 16'	
	20	25' 9" / 18'	
Drop-Tail Length	26"		
Bed Width	81-1/4"		
Floor Height	24"		
Coupler Height	18"	20"	
Ramps	3" C-Channel		
OPTIONS			
Spare Tire	Matching Tire and Rim Also Available U-Bolt Carrier		
Ball Coupler	Pintle Eye or 2-5/16 Adjustable Ball		
Wheel Type	(R) Radial	N/A	
Floor Upgrade	2X6 Oak		
Spring	Slipper Spring		
Hitch	Gooseneck Hitch		
Ramp	Spring Assist Ramp		

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.