

Implement Trailers

7 X 16
10,000 Lbs.*
12,000 Lbs.
14,000 Lbs.

7 X 18
10,000 Lbs.*
12,000 Lbs.
14,000 Lbs.

7 X 20
10,000 Lbs.*
12,000 Lbs.
14,000 Lbs.

Flat Base Ramps - Asphalt friendly design features unique flat base, 3" C-channel construction and support foot.



Shown in Optional Constructin Yellow and Forest Green.



*Actual GVWR listed on spec sheet.

Sure-Trac Implement Trailers - The frame is heavy duty structural C-channel with 3 inch channel cross members. The attention to detail in design and construction is unmatched with features like stake pockets & rub rail, sealed recessed lights, side steps, and a full frame wrap tongue. It all adds up to the best implement trailer value you can find.

Check out these other great features:

- True-Trac[™] Alignment
- 12 GA Tread Plate Fenders
- Conduit Protected Wiring
- Gel-Filled Connectors
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping



Sealed Recessed Lights
- DOT approved lights and reflective tape.



Optional Gooseneck Available



Full Seam Welds - On all joints ensure structural integrity throughout the frame.



HD 1/4" Stake Pockets
- and full-length rub rail.



Optional 7000 lb. Drop-Leg-Jack - This rugged design doubles as a spare tire mount.



HD 5 Ton D-Rings
- Welded at each corner.



New Tires, Wheels and Axles - In many states it is illegal to sell new trailers with used running gear.



Powder Coated Finish - A durable high-gloss finish that will last for years.



800-372-1755

IMPLEMENT TRAILERS SPECIFICATIONS				
		10K	12K	14K
GVWR		9990	12000	14000
GAWR		5200	6000	7000
Curb Weight	- 16	2550	2650	2750
	- 18	2750	2850	2950
	- 20	2950	3050	3150
Payload	- 16	7440	9350	11250
	- 18	7240	9150	11050
	- 20	7040	8950	10850
Max Hitch Weight		1000	1200	1400
Frame		5" C-Ch.	6" C-Channel	
Cross Members		2 ft. On-Ctr	3" C-Ch. (16 On-Ctr)	
Tongue		5" C-Ch.	6" C-Channel	
Coupler		2 5/16 A-Frame		
Jack		Coupler Mounted Jack		
Fenders		HD Tread Plate		
Axles		Easy Lube Cambered Brake		
Suspension		Eye to Eye Spring		
Tires		225/75D15 LRD (D) Bias	7.5-16 LRF Bias	235/80*16 (R) Radial LRE
Wheels		6 Lug on 5.5	8 Lug on 6.5	
		White or Grey, Modular		
Floor		2 X 6 Treated Pine		
Lights		Rubber Mounted/Sealed DOT stop, Tail, Turn, Marking and Clearance.		
Electric Plug		7 Way Round		
Finish		Powder Coated High Gloss		
Length Overall/Flat	- 16	21' 9" / 14'		
	- 18	23' 9" / 16'		
	- 20	25' 9" / 18'		
Drop-Tail Length		26"		
Bed Width		81-1/4"		
Floor Height		24"		
Coupler Height		18"	20"	
Ramps		3" C-Channel		
OPTIONS				
Spare Tire		Matching Tire and Rim - Also Available U-Bolt Carrier		
Ball Coupler		Pintle Eye or 2-5/16 Adjustable Ball		
Wheel Type		(R) Radial	N/A	
Floor Upgrade		2 X 6 Oak		
Spring		Slipper Spring		
Hitch		Gooseneck Hitch		
Ramp		Spring Assist Ramp		

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.