

Tilt Bed Equipment Trailers



**POWDER
COATED
TOUGH™**

7 X 18 + 4	7 X 18
10000 Lbs.	10000 Lbs.
12000 Lbs.	12000 Lbs.
14000 Lbs.	14000 Lbs.

Sure-Trac Tilt Bed Equipment Trailers - Our Tilt Bed Equipment trailer is built to handle your most demanding work load. Our trailer has a gravity down bed nested securely inside an amazingly strong heavy duty 6 inch C-channel frame. This trailer allows an operator to load heavy and dangerous equipment without cumbersome ramps or gates. The bed is cushioned as it gently comes to rest using a hydraulic dampening cylinder. The cylinder is mounted to a heavy duty 3 x 3 x 1/4 inch tube for added strength and security. The pivot hinge has grease zerks for easy maintenance to provide a lifetime of trouble free smooth rotation. The loading Knife Edge deck plate is a heavy 5/16 tread plate with 1/4 inch gusset transition supports to support the heavy equipment this trailer is designed to carry.

Check out these other great features:

- True-Trac™ Alignment
- 12 GA Tread Plate Fenders
- Conduit Protected Wiring
- Gel-Filled Connectors
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping



Sealed Recessed Lights
- DOT approved lights and reflective tape.



Optional Gooseneck Available



Full Seam Welds - On all joints ensure structural integrity throughout the frame.



HD 1/4" Stake Pockets
- and full-length rub rail.



Optional 7000 lb. Drop-Leg-Jack - This rugged design doubles as a spare tire mount.



Single Handle CamLoc™
- Locks bed in place.



New Tires, Wheels and Axles - In many states it is illegal to sell new trailers with used running gear.



Powder Coated Finish - A durable high-gloss finish that will last for years.

Novae

1-800-372-1755

WWW.SURE-TRAC.COM

800-372-1755

TILT BED EQUIPMENT TRAILERS SPECIFICATIONS			
	10K	12K	14K
GVWR	9990	12000	14000
GAWR	5200	6000	7000
Curb Weight	18	3080	3180
	18 + 4	3680	3780
Payload	18	6919	8820
	18 + 4	6319	8220
Max Hitch Weight	1000	1200	1400
Frame	6" C-Channel		
Cross Members	3" C-Ch. (16 On-Ctr)		
Tongue	6" C-Channel		
Coupler	2 5/16 A-Frame		
Jack	Coupler Mounted Jack		
Fenders	HD Tread Plate		
Axles	Easy Lube Cambered Brake, 4" drop		
Suspension	Eye to Eye Spring		
Tires	225/75D15	7.5-16	235/80*16
	(D) Bias	Bias	(R) Radial
	LRD	LRF	LRE
Wheels	6 Lug on 5.5	8 Lug on 6.5	
	16 X 6K, White or Grey, Modular		
Floor	2X6 Treated Pine		
Lights	Rubber Mounted/Sealed DOT stop, Tail, Turn, Marking and Clearance.		
Electric Plug	7 Way Round		
Finish	Powder Coated High Gloss		
Length Overall/Bed	18	23'9"/18.5'	
	18 + 4	27'9"/4' + 18.5'	
Between Fenders	81-1/4"		
Floor Height	20"		
Coupler Height	18"	20"	

OPTIONS	
Spare Tire	Matching Tire and Rim Also Available U-Bolt Carrier
Ball Coupler	Pintle Eye or 2-5/16 Adjustable Ball
Wheel Type	(R) Radial N/A
Floor Upgrade	2X6 Oak
Spring	Slipper Spring
Hitch	Gooseneck Hitch

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.