

Tube Top Angle Iron Trailers

- 5 X 8
2000 Lbs.
- 5 X 10
3000 Lbs.*
- 6 X 10
3000 Lbs.*
- 6 X 12
3000 Lbs.*
- 7 X 12
3000 Lbs.*
- 7 X 16
7000 Lbs.
- 7 X 18
7000 Lbs.
- 7 X 20
7000 Lbs.

*Actual GVWR listed on spec sheet.



Finished Corners – Integrated into the structural frame work. Adds strength, durability and smooth good looks.



Sure-Trac Tube Top Angle Iron Trailers - These trailers combine the strength and rigidity of our Tube Frame trailer with the economy of our Angle Iron Trailer. The tubular top rail is full seam welded to tubular uprights and tied to a tubular crossmember to help torsionally enhance the frame. All corners are welded solid which provides exclusive good looks and unmatched strength in their class.

Check out these other great features:

- EZ-Lube Hubs
- True-Trac Alignment
- Square and Teardrop Fenders
- Heavy Duty Deck Screws
- New Tires, Wheels and Axles
- Quality Crafted in Indiana
- Superior Customer Service
- Same Day Parts Shipping



Set-Back Tongue Jack - Clearance for tailgate and SUV rear doors.



Self-Retained Gate Pins - Fast, reliable and never lost.



Protected Wiring - All wires in frame tubes with corrosion resistant **Gel-Filled Connectors**.



Fold Flat Tube Frame Ramp Gate 20% lighter and 40% stronger! Saves gas when not in use. Offers clearance for oversize loads.



Full Seam Welds - on all joints ensure structural integrity throughout the frame.



Sealed Lights - DOT approved lights and reflectors.

Powder Coated Finish - All Sure-Trac trailers are powder coated for a durable high-gloss finish that will last for years.



WWW.SURE-TRAC.COM 800-372-1755



Novae[®]
NovaeCorp.com

800-372-1755

TUBE TOP ANGLE IRON TRAILER SPECIFICATIONS									
	5 x 8	5 x 10	6 x 10	6 x 12	7 x 12	7 x 16	7 x 18	7 x 20	
Type	Tube Top Single Axle					Tube Top Tandem			
GVWR	2000	2990				7000			
GAWR	2000	3500							
Curb Weight	585	725	990	1030	1090	1785	2000	2180	
Payload	1415	2265	2000	1960	1900	5215	5000	4820	
Max. Hitch Wt.	200	300				700			
Frame	3 x 2 x 3/16 Angle					3 x 2 x 1/4 Angle	4 x 3 x 1/4 Angle		
Crossmembers	3 x 2 x 3/16 Angle								
Top Rail	2 x 2 Tube								
Tongue	A-Frame 3" Channel					A-Frame 4" Channel Tongue Wrap			
Uprights	3 x 2 x 3/16 Angle and 2 x 2 x 1/8 Angle								
Coupler	2" Ball					2 - 5/16" Ball			
Jack	Set Back 2000# Top Wind								
Fenders	Square Rolled with Back					Teardrop Rolled with Back			
Axles	Cambered Idler with Brake Flange					Cambered Brake and Idler			
Suspension	Leaf Spring					Equalized Leaf Spring			
Tires	175/80D13 LRC	205/75D15 LRC							
Wheels	13 in.	15 in.							
	White, Spoke or Modular								
Floor	2 x 6 Pressure Treated Pine								
Lights	Rubber Mounted, Recessed, Sealed DOT Stop, Tail, Turn, Marking, Clearance								
Electric Plug	4 Way Flat					7 Way Round			
Finish	Powder Coated High Gloss Black								
Overall Length	137	161	185		233	257	281		
Bed Length	96	120	144		192	216	240		
Bed Width	62		71.5		81.5				
Floor Height	16	18							
Coupler Height	14	16							
Gate	2 x 2 Tubing, Mesh Covered, Full Width Ramp Gate, Fold Flat								
OPTIONS									
Wheel Upgrades	205/75D15 LRC	15" Wheels ST225/75D15 LRC							
Spare Tire Option	Matching Tire and Rim, Also Available - U-Bolt Carrier								
Brake Upgrades	N/A	Includes Breakaway Kit, 7 Way Plug, Brake Axle				Includes Second Brake Axle			

Table Units: Weights in Lbs., Dimensions as marked. Specifications subject to change without notice.